

ZACLON LLC

ZACLON[®] WETTING AGENT A

ZACLON[®] Wetting Agent A is especially prepared for use in acidic surface preparation baths such as acid rinse water and preflux solutions. The optimum use concentration range is 0.01 to 0.03% by volume (0.1 gallon to 0.3 gallon Wetting Agent A per 1000 gallons [0.1L to 0.3L Wetting Agent A per 1000L] preflux or rinse solution). To assure better mixing of the viscous wetting agent, it should be blended in ten parts of hot water before adding to large galvanizing plant tanks. Excessive agitation will cause excess foam.

Used in the preflux, Wetting Agent A will assure complete coverage of the work immersed in the bath with a preflux film and better drainage when it is withdrawn. Complete coverage will help improve zinc coating quality while better drainage will reduce preflux consumption and, by assisting drying, reduce spattering at the kettle. A thin foam blanket on the preflux bath will insulate the bath to reduce heating costs.

Used in the acid rinse water Wetting Agent A will improve rinsing and reduce dragout of contaminants such as acid, sulfates and iron into your preflux solution.

ZACLON[®] Wetting Agent A is not recommended for use in hydrochloric or sulfuric acid pickling baths. Pickling and stripping action cause evolution of hydrogen gas which can be trapped in the foam bubbles of the Wetting Agent A making the foam flammable.

The information set forth herein is furnished free of charge and is based on technical data that Zaclon LLC believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

PERSONAL SAFETY AND FIRST AID

HEALTH HAZARDS

ZACLON® Wetting Agent A causes irritation of the eyes, skin, nose, and throat. Overexposure to these products may cause liver and anaesthetic effects and may cause dizziness, headache, and nausea.

SAFETY PRECAUTIONS

Avoid contact with the eyes and skin. Avoid breathing mists or vapors.

FIRST AID

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician. For skin, flush with water.

If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen, and call a physician.

If swallowed, do not induce vomiting. Immediately give two glasses of water, or activated charcoal slurry. Never give anything by mouth to an unconscious person. Call a physician.

INSTRUCTIONS TO PHYSICIANS

To prepare activated charcoal slurry, suspend 50 g activated charcoal in 400 ml water in plastic bottle and shake well. Administer 5 ml/kg, or 350 ml for an average adult.

Due to changing governmental regulations, such as those of the Department of Transportation, Department of Labor, U.S. Environmental Protection Agency and the Food and Drug Administration, references herein to governmental regulations may be superseded. You should consult and follow the current governmental regulations, such as Hazardous Classification, Labeling, Food Use Clearances, Worker Exposure Limitations and Waste Disposal Procedures for the up-to-date requirements for the products described in this literature.

CONTACTING ZACLON LLC

For placing orders or requesting additional product information, please contact us as shown below.

ON THE INTERNET: www.zaclon.com

Email Customer Service: krosati@zaclon.com

BY PHONE:

Toll Free In Continental U.S.: (800) 356-7327

From outside United States: (216) 271-1715

BY MAIL:

Zaclon LLC

Customer Service

2981 Independence Road

Cleveland, Ohio 44115